

# Molded X-Base Table



## SPECIFICATIONS



Model	Dimensions	Weight
XB3636-MA	36"L x 36"W x 31.1"H	97 lbs
XB4200-MA	42" Diameter x 31.1"H	100 lbs
XB4242 -MA	42"L x 42"W x 31.1"H	116 lbs
XB4800-MA	48" Diameter x 31.1"H	118 lbs

\*Intended for indoor use only



## DETAILS

### Color

See Design Guide for finish options.

\*Due to differences in monitors, printers and materials, actual product colors may vary. Color chips are available for more accurate depiction of color.

### Options

Bolt-Down, Factory Ballasting (150 lbs)

\*Ballastable up to 200 pounds of dry sand or gravel. On site ballast materials not supplied by Norix.

### Assembly

Refer to manufacturer's instructions for assembly.

### Fabrication & Material

**Base:** Rotationally-molded polyethylene with lightly textured, maintenance-free surface which allows for easy cleaning. Specially formulated, high-impact polyethylene with ultraviolet light stabilizers (to reduce fading). Chemically resistant to blood, vinegar, urine, feces, salt solution and chlorine solution. Premium TruColor™ polymer is fully compounded for superior color consistency and durability.

**Top:** Premium M3 Grade, 45 lb. density particle board table top core is sandwiched between 1/8" thick hardboard and faced with special 0.05" thick high pressure laminate for superior quality and long term durability. Molded edge is radiused for safety and comfort, pressure fused to the top, rendering it firmly attached and highly sanitary. Embedded T-nuts secure top to base with tight steel to steel connection for maximum long term reliability. Robust 1.5" thick edge profile.

Made in the U.S.A.

### Installation

Ballast weighting required to validate warranty. Recommend 150 pounds of dry sand or gravel ballast. On site materials not supplied by Norix.

### Warranty

10 year limited replacement warranty

### Maintenance

**Top:** For routine and regular cleaning maintenance, Norix recommends the use of Simple Green® or an equivalent cleaning product.

**Base:** For routine and regular cleaning maintenance, Norix recommends the use of Simple Green® or an equivalent cleaning product. This product is bleach/water solution cleanable and suitable for use with hospital-grade disinfectants (such as Virex®, Wexcide® or Oxivir Five 16®) per manufacturers' instructions.

## TESTING

### Performance Test Standards

Product tested to 1,000 lb static load

### Environmental Test Standards

GREENGUARD and GREENGUARD Gold Certified by UL Environment. Product certified for low chemical emissions to UL 2818. UL.COM/GG

### Flammability Test Standards

- State of California, Technical Bulletin No. 133, Flammability Test Procedure for Seating Furniture for Use in Public Occupancies.
- ASTM E1537 Test method for Fire Testing of Real Scale Upholstered Furniture Items