NORIX

SPECIFICATIONS



Model

PRD600 - Prodigy* Desk with concealed anchoring for maximum security (anchoring mechanism and anchoring hardware included).

Weight

50 lbs

*Intended for indoor use only

Dimensions

Height 30" Overall Length 35.5" Overall Width 24"

Note: Dimensional tolerances are +1% due to manufacturing process.











DETAILS

Colors

See Design Guide for finish options.

*Proprietary TruGrain™ aesthetic provides authentic texture and gradation that replicates natural wood. Variations in color and finish vary from product to product and lot to lot, just like natural wood. Due to differences in monitors, printers and materials, actual product colors may vary.

Options

Factory Ballasting (50 lbs)

*Factory ballasting option must be communicated at time of order; products are not field ballastable.

Patents

Patents Pending

Fabrication & Material

One-piece, 100% seamless, specially formulated polymer construction is structurally reinforced for superior durability, impact resistance and security. Rounded edges for added safety. Each piece is uniquely fashioned with proprietary TruGrain™ polymer formulation to replicate natural wood, and deliver a residential, non-institutional appearance. The seamless, one-piece construction delivers long-term, maintenance-free performance superior to wood in infection-control, fluid, tamper, infestation, contraband resistance and ligature resistant design. Contains a minimum of 30% recycled content. Made in the U.S.A.

Installation

Proprietary ligature resistant floor anchoring system with concealed hardware (mechanism and all anchoring hardware included). Anchoring mechanism and hardware intended for concrete floors. (Please consult contractor or facility management as necessary.) Security caulk may be applied to the perimeter after anchoring.

Warranty

10 year limited replacement warranty.

Cleaning & Maintenance

For routine and regular cleaning, Norix* recommends the use of Simple Green* or an equivalent cleaning product with a soft damp cloth. Prodigy* products are suitable for use with hospital-grade disinfectants (such as Virex*, Wexcide* or Oxivir Five 16*) per manufacturers' instructions.

TESTING

Environmental Test Standards

• GREENGUARD and GREENGUARD Gold Certified by UL Environment. Product certified for low chemical emissions to UL 2818, UL.COM/GG

Performance Test Standards

Tested to 1,000 lbs static load

Flammability Test Standards

- State of California, Technical Bulletin No. 133, Flammability Test Procedure for Seating Furniture for Use in Public Occupancies
- State of California, Technical Bulletin No. 117, Flammability Test Procedure for Seating Furniture for Use in Public Occupancies
- State of California, Technical Bulletin No. 116, Flammability Test Procedure for Seating Furniture for Use in Public Occupancies
- \bullet ASTM E1537 Test Method for Fire testing of Real Scale Upholstered Furniture Items
- NFPA 261 Cigarette Ignition Resistance of Upholstered Furniture